

Simulation of Experiments on Passive Focusing of TNSA-Produced Proton Beams

R. H. Cohen, A. Yuen, C. Belli, S. M. Lund, P. A. Ni

July 10, 2013

55th Annual Meeting of the APS Division of Plasma Physics Denver, CO, United States November 11, 2013 through November 15, 2013

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Abstract Submitted for the IT05 Meeting of The American Physical Society

Sorting Category: 3.0 (C)

Simulation of Experiments on Passive Focusing of TNSA-Produced Proton Beams¹ RONALD COHEN², A. YUEN, C. BELLEI, S. M. LUND, LLNL, P. A. NI, LBNL — Intense proton or ion beams can be propagated through a sequence of thin metallic foils to collimate or focus the beam. The foils attenuate the beam's defocusing electrostatic field while not suppressing the focusing magnetic force. Results from recent experiments³ with TNSA-produced proton beams are qualitatively consistent with this process: the foils substantially reduce the observed spot size. We present simulations of these experiments done with the WARP and LSP particle-in-cell codes. LSP is used to simulate the initial evolution of protons and electrons produced in the TNSA process; the resulting proton distribution provides initial conditions for WARP, which then follows the protons and initially co-moving electrons through the foil stack and beyond to a set of diagnostic films. WARP is run with quasi-static electric and magnetic fields. Effects incorporated in the simulations include field-emitted and knock-on electrons, scattering and slowing down of protons and electrons in the foils, and saturation effects in the diagnostic films. With all of these effects in place we obtain simulation results (spot size versus energy) that are consistent within uncertainties to the experimental measurements.

¹Work performed for USDOE under contracts DE-AC52-07NA27344 at LLNL and DE-AC02-05CH11231 at LBNL ²Retired

³P.A. Ni, invited talk, this meeting

Abstract	Limit
Prefer Oral Session X Prefer Poster Session	Ronald Cohen rhcohen@lbl.gov LLNL (Retired)
Date submitted: 09 Jul 2013	Electronic form version 1.4